MINCO PIPE, INC.

MATERIAL SAFETY DATA SHEET

Issued By:

MINCO SAFETY DEPARTMENT 3400 W. Marshall Ave.

Suite #428

Longview, TX. 75604

Contact:

Vikki Joyce 903-759-2711

Emergency #:
Approved By:

Issue Date:

Nov. 9, 2012

Revised Date:

SECTION I-MATERIAL IDENTIFICATION

PRODUCT NAME OR NUMBER (AS IT APPEARS ON LABEL):

Minco Pipe Burning Bars and Lance Pipe

(310-xxxxx)

MANUFACTURER'S NAME

EMERGENCY PHONE NUMBER

Minco Pipe, Inc. (903-759-2711)

ADDRESS (Number, Street, City, State, and Zip Code)

3400 W. Marshall Ave.

HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD NO. (49CFR 172.101)

ADDITIONAL HAZARD CLASSES (As applicable)

N/A

CHEMICAL FAMILY

FORMULA

Inorganic Chemical

N/A

SECTION II-INGREDIENTS

CAS#	CHEMICAL NAME	PEL(mg/m3)	TLV(mg/m3)	%W
7439-89-6	Iron	None Established		97-99.5
1137 67 6	11011	None Established	5mg/cu	10/mg/cu.m 0614
7440-44-0	Carbon	15mg/cu.m		10mg/cu.m
7440-21-3	Silicon	15mg/cu.m	10mg/cu	1.8-4.0
7439-96-5	Manganese	C5 mg/cu.m	C5mg/cu	<1.2
		(as dust)	(as dust)	
2451529052505				0.01-1.5
7440-02-0	Nickel		lmg/cu.m	Img/cu.m
7440-47-3	Chromium	.1mg/cu.m	.5mg/cu.m	0.02-1.13
	Chromium (Hexavalent)	None Established	.5mg/cu	
7439-98-7	Molybdenum	5mg/cu.m	10mg/cu	0.01-0.75
7704-34-0	Sulfur (dioxide)	5 p.p.m	None Established	0.02
7723-14-0	Phosphorus	.1mg/cu.m	.1mg/cu	< 0.05

SECTION III - PHYSICAL HAZARDS (REACTIVITY DATE)

1309-38-2	Iron Oxide	5mg/cu.m	10mg/cu.m
124-30-9	Carbon Dioxide	5000 p.p.m.	5000 p.p.m
630-08-0	Carbon Monoxide	50 p.p.m	59 p.p.m

	SECTION :	IV-PHYSI	CAL DATA
BOILING POINTN/A		SPECIFIC	C GRAVITY (H2O=1)
VAPOR PRESSURE_	N/A		
PERCENT VOLATILE	BY VOLUME	(%)	0
PERCENT SOLID BY	WEIGHT	(%)	100
VAPOR DENSITY		(AIR=1)	N/A
EVAPORATION RATE		(=1)	N/A
SOLUBILITY IN WAT	ER	pH=	N/A
APPEARANCE AND O	DOR		
MATERIAL IS:	Solid		

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	None	MET	HOD US	ED	N/A
FLAMMABLE UNITS_	None	LEL	N/A	UEL	N/A
EXTINGUISHING MED	[AU:	se Carbon Dio	xide, Water	, or Foam	
SPECIAL FIRE FIGHTI wear a NIOSH approved, Self C	NG PROCE	EDURES_	If entering	g a confined area	a, fire fighters should
UNUSUAL FIRE AND EX				None	

SECTION V-HEALTH HAZARD DATA

The ACGIH recommended TLV for cutting fume NOC (Not otherwise classified) is mg/cu.m. See reactivity data for specific fume constituents which may modify PEL/TLV.

Acute over Exposure---to cutting fumes may result in discomfort such as nausea, dryness or irriation of nose, throat oe eyes. In confine area, may cause unconsciousness and death.

Chronic over exposure---to cutting fumes may lead to siderosis and may reduce pulmonary function.

Emergency/ First aid Procedures---Provide oxygen if breathing is labor, give artificial respiration and get medical help. Treat skin areas exposure burns. Obtain medical aid for all overexposures and eye injuries

SECTION VII-SPILL OR LEAK PROCEDURES

WASTE DISPOSAL METHOD La	ndfill in accordance with local, state, and federal regulations
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) None
VOLATILE ORGANIC COMPOUN	D (VOC) (AS PACKAGED MINUS WATER) None

RESPIRATORY PROTECTION (SPECIFY TYPE) Respirator if welding

SPECIAL
DN DAG 5 PROMES NO
OTHER
Use heat resistant gloves during use
GLASSES ARE RECOMMENDED)
tive clothing
AL PRECAUTIONS
1

TIPSITET ATTACAL

The above information was extracted from Material Safety Data Sheets from our raw material suppliers and is believed to be correct as of the date hereof.

However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assume the risk of his use thereof.